

**Complies with the requirements of**  
AS3894.1-2002 and Nace Standards: TM0186-94; TM0384-94;  
RP0490-2001; RP0274-98 & RP0188-99

# NEW RELEASE




### Applications

- Used for detection of coating porosity (pin-holes, or holidays) in dielectric (insulation type) coatings on conductive substrates, including concrete.
- Regulated 'Pulsed' output fully adjustable  
Ideal for use:
  - In moist conditions
  - On wet coating surfaces
  - On contaminated coating surfaces
  - On carbon-impregnated coatings, ie: carbonated rubber
  - On 'plastic'/fibreglass type coatings likely to become electrostatically charged
  - Coating Thickness Range: 150 to 25,000µm using P40 model

### Controls

- 1 LED display
- 2 On/Battery condition indicator Light
- 3 Visual alarm indicates when fault is found
- 4 Voltage Up
- 5 Voltage Down
- 6 Off
- 7 On
- 8 Audible alarm when fault is found
- 9 Earphone (connected on opposite side)
- 10 Fuse (2.5A slow blow) 5 x 20mm
- 11 Earth connection point
- 12 Alarm sensitivity 'wet' or 'dry' conditions (located in battery compartment)
- 13 Charge connector
- 14 Clip-on power pack



CONTROL LAYOUT



SIDE VIEW

### Features

- Lightweight with ABS case
- LED display of voltage
- Voltage ranges from 500v to 20kV or 40kV, fully adjustable
- Clip-on battery pack
- Constant test current
- Overcharge protection
- Earphones for noisy environments

### Complete with

#### Industrial Kit:

Detector with clip-on power pack, 10hr Charger, Probe Handle with 2m lead, 60mm Connector for flat brushes, 7m Earth lead with clamp, Fan Brush, 250mm Flat brass wire brush, 450mm Probe extension, Air-operated earphones, Shoulder & Waist Harness, Kit Case, Operating instructions with conformance certificate.

### Specifications

	P20	P40
Unit weight:	2.2kg	2.2kg
Packed weight:	6.0kg	6.0kg
Display:	LED	LED
Voltage:	1 to 20kv	5 to 40kv
Resolution:	100v	100v
Alarm range:	1 to 20kV	5 to 40kV
Short circuit test current:	1.5mA max	
Power supply:	Gel Cell 3Ah Clip On	
Dimensions:	260 x 160 x 70mm	
Alarm:	Audible	
Probe handle:	Rubber lead	
Battery condition:	LED Indicator	

Made in **AUSTRALIA**

**PCWI International Pty Ltd**

13 Alhambra Avenue CARDIFF NSW 2285

Ph: (02) 4954 3900 • Fax: (02) 4954 3999

email: sales@pcwi.com.au • http://www.pcwi.com.au



**KE-TECH Kft.**

H-1183 Budapest, Üllői út 470.

Tel.: (+36-1) 290-0151, Fax: (+36-1) 292-2159

E-mail: ketech@ketech.hu, www.ketech.hu